

Amendments to the Claims

Claim 1 (Currently Amended) A fuel cell power generation apparatus equipped with a fuel reforming device and a fuel cell body, the fuel cell power generation apparatus comprising:

raw gas feeding means for feeding into the fuel reforming device at least one raw gas of ~~among~~ a burner exhaust gas discharged from a heating burner of the fuel reforming device, exhaust air discharged from a cathode of the fuel cell body, and air from outside the fuel cell power generation apparatus;

inert gas formation means including an oxidizable and reducible oxygen adsorbent which adsorbs oxygen in the at least one raw gas to remove oxygen from the at least one raw gas and generate an inert gas; and

adsorbent reduction means for reducing the oxygen adsorbent, which has adsorbed oxygen, by use of a reformed gas reformed in the fuel reforming device or an anode exhaust gas discharged from an anode of the fuel cell body, wherein

the oxygen adsorbent comprises at least one of chromium (Cr), manganese (Mn), iron (Fe), cobalt (Co), nickel (Ni), copper (Cu), and zinc (Zn).

Claim 2 (Canceled)

Claim 3 (Currently Amended) The fuel cell power generation apparatus according to claim 1, wherein

the oxygen adsorbent is disposed in at least one of ~~location among~~ a location in said raw gas feeding means, a location between a reforming catalyst layer and a CO conversion catalyst layer provided in the fuel reforming device, a location upstream of the reforming catalyst layer within the fuel reforming device, and a location in the reforming catalyst layer provided in the fuel reforming device.

Claims 4-9 (Canceled)

Claim 10 (**Withdrawn - Previously Presented**) A method for operating the fuel cell power generation apparatus of claim 1, the method comprising:

- forming the inert gas by said inert gas formation means; and
- removing residual matter, which has remained within the fuel reforming device, with the inert gas for inert gas purging, in stopping an operation for power generation.

Claim 11 (**Withdrawn - Previously Presented**) The method according to claim 10, further comprising:

- reducing the oxygen adsorbent of said inert gas formation means with the reformed gas formed by reforming in the fuel reforming device or the anode exhaust gas discharged from the anode of the fuel cell body, thereby performing regeneration of the oxygen adsorbent of said inert gas formation means.

Claim 12 (**Withdrawn - Previously Presented**) The method according to claim 11, further comprising:

- performing said reducing in carrying out an operation for power generation.

Claims 13-16 (**Canceled**)

Claim 17 (**Withdrawn - Previously Presented**) The method according to claim 10, wherein said removing comprises:

- removing the residual matter within the fuel reforming device with steam; and
- then purging an interior of the fuel reforming device with the inert gas.

Claim 18 and 19 (**Canceled**)

Claim 20 (**Withdrawn - Previously Presented**) The method according to claim 17, wherein said removing comprises:

- removing the residual matter within the fuel reforming device with the steam;
- then flowing only air to the heating burner of the fuel reforming device to cool the fuel reforming device; and

then purging the interior of the fuel reforming device with the inert gas.

Claim 21 and 22 (**Canceled**)

Claim 23 (**Withdrawn - Previously Presented**) The method according to claim 17, wherein the steam for removing the residual matter within the fuel reforming device has a fuel gas incorporated therein, the fuel gas being in an amount necessary and sufficient to prevent oxidation within the fuel reforming device.

Claims 24 and 25 (**Canceled**)

Claim 26 (**Withdrawn - Previously Presented**) The method according to claim 10, further comprising:

actuating only the heating burner of the fuel reforming device to heat and raise a temperature of the fuel reforming device;

feeding steam to the fuel reforming device during a rise in the temperature of the fuel reforming device, the steam containing a necessary and sufficient amount of a fuel gas to prevent oxidation within the fuel reforming device; and

supplying the fuel gas, in a necessary amount according to actuation of the fuel cell body, after completion of the rise in the temperature of the fuel reforming device, to start an operation for power generation.

Claims 27 and 28 (**Canceled**)

Claim 29 (**Previously Presented**) The fuel cell power generation apparatus according to claim 1, wherein

said adsorbent reduction means includes a heater for heating the oxygen adsorbent.

Claim 30 (**Previously Presented**) The fuel cell power generation apparatus according to claim 1, wherein

the oxygen adsorbent is located adjacent to the fuel reforming device such that the oxygen adsorbent is heated by heat of the fuel reforming device.